



EVO-CONCEPT Pass-through Dishwasher - CO-142HRBDD

Quick Overview

EVO-CONCEPT pass-through dishwasher with drain pump and detergent dispenser

- Hourly production: 60 baskets/hour - 720 dishes/hour
- Clearance (max ware height): 440mm
- Wash cycles: 55-75-120 seconds
- Double rotating wash and rinse systems, made of AISI-304 stainless steel
- Water consumption: 2.4 litres/rinse
- Safety magnetic switch for hood opening
- Adjustable legs
- Supplied with 1 base basket; 1 plate basket and 2 cutlery containers
- WaterMark approved
- Canopy assembly required

Description

EVO-CONCEPT pass-through dishwasher with drain pump and detergent dispenser

Key Features

- Hood-Type dishwashers with heat recovery system
- EVO Generation
- Constructed in stainless steel.
- Counterbalanced hood with handle and spring system.
- Stainless steel double rotating wash and rinse system, top and bottom.
- 440 mm hood opening (suitable for GN 1/1 trays).
- Continuous wash cycle.
- High water flow wash pump
- Rounded tank to facilitate washing and drainage.

- Stainless steel armoured heating elements in the wash tank and rinse boiler.
- (Optional) Multi-voltage: Allows the machine to be connected to a single-phase or three-phase voltage network.
- AISI-304 stainless steel filter trays in the wash tank.
- Thermostatic controlled temperatures (wash, 60 ° C, and rinse, 90 ° C).
- Thermal stop system which guarantees a rinse temperature of 85 ° C.
- Safety stop switch in hood opening.
- Safety thermostat - Machine with control panel and electronic control
- 55 " , 75 " and 120 " wash cycles.
- Theoretical maximum production of 65 baskets/hour (1170 plates/h).
- 2.4 litre water consumption per cycle.
- Rinse with thermostop system.
- Standard factory setting disabled. Easy to enable.
- Alternating or simultaneous tank and boiler heating.
- IPX4 anti-humidity protection.
- Energy recovery device
- Drainage pump
- Tank emptying program.
- Peristaltic detergent doser.
- Equipment included: One base basket, one basket for plates and two cutlery holder

2 Years Parts and Labour Warranty

Your Shipping Specifications

Net Weight (Kg)	126
Width (mm)	630
Depth (mm)	750
Height (mm)	11920
Packing Width (mm)	905
Packing Depth (mm)	825
Packing Height (mm)	1720
Power	11.1/3-N kW/A
Warranty	2 Years Parts and Labour