





FED-X S/S Double Door Upright Fridge - XURC1200SFV

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- · Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- · User friendly Digital controls and internal lighting
- · Integrated door handle for easy cleaning
- · Heavy duty evaporator and condenser fans
- · Heavy duty castors with front wheel brakes
- · Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H

Description

FED-X S/S Double Door Upright Fridge - XURC1200SFV

- Net Capacity: 1200L
- · Cooling System: Fan forced cooling
- Temperature range: -2~+8 ° C
- Compressor: CubigelController: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Refrigerant: R290
- · Stainless steel interior and exterior with rounded corners for easy cleaning
- · Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- · User friendly Digital controls and internal lighting
- Integrated door handle for easy cleaning
- Heavy duty evaporator and condenser fans
- · Heavy duty castors with front wheel brakes
- · Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H

1



Your Shipping Specifications

Net Weight (Kg)	167
Width (mm)	1340
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	1365
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 10A; 430W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice