



FED-X S/S Four Door Bench Fridge - XUB6C22S4V

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Unit can be placed against wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1669mm W x 480mm D x 564mm H

Description

FED-X Stainless Steel Three Door Bench Fridge - XUB6C22S4V

- Net Capacity: 449L
- Cooling System: Fan forced cooling
- Temperature range: -2~+8 ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Unit can be placed against wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1669mm W x 480mm D x 564mm H

Your Shipping Specifications

Net Weight (Kg)	121
Width (mm)	2230
Depth (mm)	600
Height (mm)	850
Packing Width (mm)	2260
Packing Depth (mm)	630
Packing Height (mm)	910
Power	240V; 50V; 10A; 345W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice