



## FED-X S/S Four Door Upright Freezer - XURF1200S2V

### Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running cost by up to 30%

### Description

#### FED-X S/S Four Door Upright Freezer - XURF1200S2V

- Net Capacity: 1200L
- Cooling System: Fan forced cooling
- Temperature range: -18~-22 ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes

- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running cost by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

## Your Shipping Specifications

---

Net Weight (Kg)	177
Width (mm)	1340
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	1365
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 730W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice