



## Fagor IKORE Concept 20 Trays Combi Oven CW-201ERSWS

### Quick Overview

- 2.8" screen with rotary knob and push function for configuring and Confirming inputs
- Clima: Humidity management and control by means of direct measurement with a humidity
- 10% regulation capacity
- Storage capacity for more than 100 9-stage recipes (come with 100 recipes pre-set)
- Air and water cooldown (rapid cabinet cooling function)
- Cooking modes: low temperature steam 30-989, steam 999, super steam 100- 1309, mixed 30-3009 and convection 30-3009

### Description

A professional, configurable oven which stands out for its precision in cooking results thanks to its steam saturation system and effective climate management. It certainly marks a before and an after in the way we cook. The iKORE generation is autonomous. It includes a system of intelligent recipes and additional cooking process features, and can even be controlled remotely. And when you have finished, we guarantee maximum hygiene thanks to the innovative washing system.

### FUNCTIONS:

- 8" screen with rotary nob and push function for configuring and confirming inputs
- iClima: Humidity management and control by means of direct measurement with a humidity sensor . 10% regulation capacity
- Fagor Recipe Centre: . 100 factory preset and culinary tested recipes . Storage capacity for more than 100 9-stage recipes (come with 100 recipes pre-set)
- Air and water cool-down (rapid cabinet cooling function)
- Cooking modes: low temperature steam 30-98°, steam 99°, super steam 100- 130°, mixed 30-300° and convection 30-300°
- Chamber dehumidification for crispy roasts - Delta cooking

### DIRECTSTEAM:

- Steam generation by injecting water into the turbine, atomising the water and converting it into steam.

#### CONTROLS:

- Languages: 5
  - Ability to configure screen tone, volume and contrast.
  - Tone: 8
  - Power, network, language and system settings.
  - SAT and Trade fair mode EQUIPMENT FEATURES:
  - Stop/start function
  - EZ-Sensor. Internal probe with 4 measuring locations
  - Positioning aid for temperature sensor
  - Manual steam injection
  - Automatic humidification system
  - Variable humidification with 5 levels
  - 6 programmable air circulation speeds (from 1400 rpm to turbine stop)
  - Option to switch from °C to °F
  - Display of actual values and selected values
  - Delayed programming
  - Ability to select 1/2 power
  - Automatic humidification system
  - Automatic dehumidification system
  - Automatic adaptation to the characteristics of the installation site (altitude, etc.) including initial self-testing
  - Automatic boiling point adjustment
  - Removable fan cover
  - Integrated turbine brake for increased safety
  - HA-Control (indirect combustion, does not pass through the oven chamber)
  - Auto-reverse system for reversing fan rotation
  - Double-glazed, ventilated cooking chamber door
  - Special heat-reflective coating and hinged inner panes for easy cleaning
  - LED lighting in the cooking chamber
  - HOLD-OPEN DOOR systems (3 locking positions for greater user safety)
  - Easily replaceable gasket insert - Interior and outer material: AISI 304 stainless steel (interior mirror polished)
- CERTIFICATION AND INS

#### TALLATION SYMBOLS:

- EC declaration of conformity
- EC declaration of gas conformity
- CB safety
- IPX5 protection against splashes and jets of water
- Height adjustable equipment feet (all except 0623)
- Monitor App & Maintenance App (self-diagnosis of warnings and errors)
- Logging App: . Cycle history . Error history

## WASHING SYSTEM:

- iWashing (environmentally efficient)
- Choice of iWashing Solid or iWashing Liquid smart washing systems
- Washing programmes:
  - 1 basic cleaning programme (spray) . 3 automatic cleaning programmes . 1 rinsing programme . 1 polishing programme
- Indication of cleaning status and remaining time

2 Years Parts and Labour Warranty

## Your Shipping Specifications

---

Net Weight (Kg)	249
Width (mm)	898
Depth (mm)	817
Height (mm)	1841
Packing Width (mm)	1095
Packing Depth (mm)	1015
Packing Height (mm)	2070
Power	415V/50Hz; 37.2kW;3N
Warranty	2 Years Parts and Labour