

Vacc-Safe Medical refrigerators are suitable for storing vaccines, medicines and laboratory products between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Self Closing Door

Avoid letting the heat in by accident.



Security

Audible and Visual Alarms. Safety Lock.



Single LED Display

High accuracy single LED displays.



DC Turbo Fan

Decreases noise level by 8% while increasing efficiency.



Lockable

Additional security for pharmaceuticals and samples.



USB Data

Built in USB Data Logger. Data can be traced and exported.

High Precision Temperature Control.

Vacc-Safe vaccine and medical cooling storage enables high precision temperature control and accuracy within 0.1°C giving the utmost confidence that goods are stored with precision. LBA Foaming Technology provides more effective insulation to improve performance and reduce overall energy consumption.



Low-E glass door.

Low-E means 'Low Emissivity' which enables a reduction in the transport of heat or cold through the glass. Simply put it helps to reduce condensation appearing on the inside of the door when opened.



Specific Temperature Range For Cosmetics.

This product is perfect for the storage of Cosmetic Injectable products as it can be set at the ideal temperature range of 2-6°C for cosmetics storage.

Increased Product Lifespan

Powerful heat dissipation for the condenser improving heat exchange capacity by more than 20% over that of common copper tube fin condensers.

Item	Model No.	BT42
Product structure data	Temperature Range	2~ 6°C
	Fridge Storage Volume(L)	42L Nett
	Product Dimensions(mm)(wxdxh)	480*450*550
	Interior Dimensions(mm)(wxdxh)	400*345*380
	Packing Dimensions(mm)(wxdxh)	525*490*670
	Net/Gross Weight	25/29
Technical data	Compressor type	Fixed frequency
	Cooling Type	Forced air cooling
	Defrost type	No frost
	Climate Class	N
	Rated Voltage/Frequency(V/Hz)	220V/50Hz
	Rated Power(W)	65
	Rated Current(A)	0.75
	Decibel rating	35
	Refrigerant/Amount(g)	R600a/18g
Control	Temp HI/LOW reset	Y
	Sensor Qty	2
	Controller	Microprocessor
	Display	LED display
Product Performance	Temperature Accuracy	0.1 °C
	Temperature uniformity/°C	≤3.5°C
	Sound Alarm	Y
Alarms	Light Alarm	Y
	Power Failure Alarm	Y
	Sensor Failure Alarm	Y
	Environment Temperature Alarm	Y
	Door ajar Alarm	Y
	High Temperature Alarm	Y
	Low Temperature Alarm	Y
	Remote Alarm	Y
Accessories	USB	Y
	Anti-condensation Door	LOW-E glass
	Backup Battery (Controller)	Y
	Backup Battery Endurance	24h
	Shelves/Drawers Qty	1/1
	Cable Port	Y
	Castors/type	N

