



## Fagor Kore 900 Series Indirect Heating Boiling Pan M-G915BMLPG

### Quick Overview

Tank: 600mm x 500mm H Volume: 150L

- LPG
- Surface tops manufactured in 2mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding and polishes. Screws hidden from view
- Double walled lid balanced by means of a hinge with front handle, with diagonal opening to 75° which allows the lid to be kept open in any position
- Well stamped into the surface top by robotic welding, manufactured in 304 S/S, with the bottom of the well in AISI-316L stainless steel.
- Well filling with hot or cold water by electrovalve, activated with a single switch located on the front panel
- Well emptying by 2" safety valve with handle in athermic material and safe and effortless handling.
- Robust and reliable filter for draining the well manufactured in AISI-304 S/S. Easily extractable.
- Controls with protective base and system against water infiltration
- High temperature enameled cast iron flue protector.
- Access to the components from the front
- Machines with IPX5 grade water protection

### Description

Fagor Kore 900 Series Indirect Heating Boiling Pan M-G915BMLPG

- LPG
- Surface tops manufactured in 2mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding and polishes. Screws hidden from view
- Double walled lid balanced by means of a hinge with front handle, with diagonal opening to 75 ° which allows the lid to be kept open in any position
- Well stamped into the surface top by robotic welding, manufactured in 304 S/S, with the bottom of the well in AISI-316L stainless steel.
- Well filling with hot or cold water by electrovalve, activated with a single switch located on the front panel
- Well emptying by 2" safety valve with handle in athermic material and safe and effortless handling.
- Robust and reliable filter for draining the well manufactured in AISI-304 S/S. Easily extractable.
- Controls with protective base and system against water infiltration
- High temperature enameled cast iron flue protector.
- Access to the components from the front
- Machines with IPX5 grade water protection
- Group of optimised combustion stainless steel tubular burners, controlled by energy regulator and by pressure switch

- Control by energy regulator and by pressure switch, permitting lower water and energy consumption
- Ignition of group of burners by spark train

2 Year Parts and Labour + 2 Years Parts only Warranty with Product Registration

## Your Shipping Specifications

---

Net Weight (Kg)	110
Width (mm)	800
Depth (mm)	930
Height (mm)	850
Packing Width (mm)	1080
Packing Depth (mm)	900
Packing Height (mm)	1160
Power	24KW
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice